

L Numb r	Hits	Search Text	DB	Time stamp
-	363	439/92.ccls.	USPAT	2002/07/02 18:29
-	1	"5460543".PN.	USPAT	2002/07/02 18:23
-	1	"5345366".PN.	USPAT	2002/07/02 18:23
-	1	"5022873".PN.	USPAT	2002/07/02 18:27
-	1	"4938703".PN.	USPAT	2002/07/02 18:28
-	1	"4855873".PN.	USPAT	2002/07/02 18:29
-	1	"4403761".PN.	USPAT	2002/07/02 18:29
-	16	"4938703"	USPAT	2002/07/02 18:29
-	3	"5984697"	USPAT	2002/07/02 18:37
-	244	174/138D.ccls.	USPAT	2002/07/22 14:31
-	274	174/138G.ccls.	USPAT	2002/07/22 16:25
-	1016	circuit adj board with clip	USPAT	2002/07/22 16:25
-	42	(circuit adj board with clip) and (ground adj clip)	USPAT	2002/07/22 16:28
-	19	standoff and (ground adj clip)	USPAT	2002/07/22 16:28

Positioning through hole

is interpreted as

positioning using d hole

In this case positioning is provided by a screw attachment
a mounting post through the hole

Alternatively,

In the other embodiment, which is not
precluded by the prior art, a screw can be
located at the mounting post with a nut on
a top of the board.